

Spring Action Valve Knee Operated F&F 15mm - Straight Lever

Hands-free, knee operated tapware is a self-closing spring action mechanism. Constructed from dezincification resistant (DR) brass with a durable chrome plated finish.

Choose from Enware's range of outlets to suit your application and WELS water efficiency requirements.

KEY FEATURES

- Vandal resistant design
- Self-closing spring action mechanism
- DR Brass construction



PRODUCT CODE

BUB268L

Spring Action Valve Knee Operated F&F
15mm - Straight Lever



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.

TECHNICAL DATA

Inlet Connection	1/2" BSP (15mm)
Outlet Connection	1/2" BSP (15mm)
Recommended Pressure	50 kPa – 500 kPa
Maximum Static Pressure	1200kPa
Flow Rate	8 L/min
Recommended Temperature	5°C - 30°C
Maximum Working Temperature	85°C
Finish	Chrome
Valve Type	Spring Action

