


# Concealed Spindle Recess Set with SP110 Swivel Aerated Spout - 1/2 Turn Ceramic Disc

Concealed spindle tapware series is robust and vandal resistant. The ergonomically designed handle features a dress skirt which conceals the anti-vandal handle fixing and spindle.

Ideal for commercial, institutional and public amenity applications.

## KEY FEATURES

- Half-turn ceramic disc
- High quality dezincification resistant (DR) brass construction
- Vandal-resistant internal locking ring secures the handle which requires special key to release (key supplied)
- Serviceable with all wearing components replaceable, thus providing an even longer life
- Blue (Cold), Red (Hot) or Yellow (Warm) coloured indicator button. (3 colour indicator buttons included)
- Heavy duty bright chrome
- 3 Star WELS rating (8 L/min) aerator



## PRODUCT CODE

CSQ315

Concealed Spindle Recess Set with SP110 Swivel Aerated Spout - 1/2 Turn Ceramic Disc



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - [www.enware.com.au/warranty](http://www.enware.com.au/warranty).

## TECHNICAL DATA

Inlet Connection	1/2" BSP (15mm)
Recommended Pressure	50kPa – 500kPa
Maximum Static Pressure	800kPa
Maximum Recommended Temperature	70°C
Maximum Ceramic Disc Working Temperature	85°C
Flow Rate	8 L/min
Finish	Chrome
Valve Type	1/2 Turn Ceramic Disc

