

Detention Hot & Cold Basin Set with SP003 Fixed Low Level Spout

Detention style Vandal Resistant Hot & Cold Basin Set with SP003 Fixed Spout - Standard Adjustable Breech and Bodies with 90mm Cast Fixed Low-Level Spout

KEY FEATURES

- Suitable for 3 tap hole basins or troughs
- Low profile secure handles



PRODUCT CODE

DET306	Detention Hot & Cold Basin Set with SP003 Fixed Low Level Spout
--------	---



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.

Detention Hot & Cold Basin Set with SP003 Fixed Low Level Spout

TECHNICAL DATA

Inlet Connection	1/2" BSP (15mm)
Recommended Pressure	50kPa – 500kPa
Maximum Static Pressure	800kPa
Maximum Recommended Temperature	70°C
Maximum Ceramic Disc Working Temperature	85°C
Flow Rate	6L/min 3.8L/min aerator supplied loose in carton
Finish	Chrome
Valve Type	1/4 Turn Ceramic Disc

* This product is not for applications that require ligature resistance
For ligature resistant applications consider wall mounted products

