

Secure Wall Mounted Sensor Tap - Hands-Free - Ligature Resistant Basin Outlet

Enware's water efficient easy-to-use secure tapware products have been designed to provide a high level of security and vandal resistant features.

They also provide smooth surfaces to remove ligature points and lessen the possibility of user harm.

KEY FEATURES

- Ideal for all Secure environments where user comfort and safety is essential
- To turn tap on, place hand under spout in front of sensor
- To turn tap off, move hand away
- Valve stays open for 6 seconds, or as long as the hand is within sensor range
- Maximum flow time of 45 seconds* per activation reduces waste and prevents vandalism
- Equipped with automatic hygiene flush function (1-10min/24hr) - enabled on request*
- Stainless steel sensor plate with vandal resistant fixings
- Anti-ligature design and anti-vandal aerator outlet
- Removal of sharp edges to reduce potential for user harm
- Spout has anti-rotation pin and high Security Torx grub screw, designed to exceed anti-ligature requirements of TS001-2013
- WELS: 3 Star Rating (8 L/min)
- Watermark: AS/NZS 3718 WMKA 1583

Anti-Pick sealant around wall face plate is recommended to provide higher level of ligature resistance

* Longer flow times, hygiene flush function and other program settings are available at the time of ordering. Contact Enware for more information.



PRODUCT CODE

DET5071A-CNBSN Secure Wall Mounted Sensor Tap - Hands-Free - Ligature Resistant Basin Outlet



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.

Secure Wall Mounted Sensor Tap - Hands-Free - Ligature Resistant Basin Outlet

TECHNICAL DATA




WELS Category	Tapware
Standard WELS	3 Stars
Standard WELS Flow Rate	8 L/min
Inlet Connection	15 mm (1/2"BSP)
Minimum Recommended Pressure	100kPa
Maximum Recommended Pressure	500kPa
Maximum Temperature	70 °C
Operating Voltage	24V DC
Maximum Current	1A
Power Consumption - Maximum Load	10W
Sensor Min / Max Ambient Temperature	Minimum: -5 °C, Maximum: 50 °C
IP Rating Front Panel and Sensor Lens	IP67
IP Rating Behind Panel	Nil
Minimum Sensor Range	100mm
Maximum Sensor Range	235mm
Flow Time	Runs as long as hand is within range. (Active Sense) When out of range, runs for 6 seconds. (Afterflow) Maximum continuous flow period per sensor activation is 45 seconds. (Security Time Out)

OPTIONAL ACCESSORIES

EMDS801	EMD Touch-Activated Control Kits - 2m Extension Lead
---------	--

SPARE PARTS

ENMS136A	Spare Parts: Active Sense Stainless Sensor Plate, Bracket, Transformer and Cables
DET667	Spare Parts: Aerator Insert and O-ring for DET660B
EMDS802	Spare Parts: Transformer Piezo 24VDC 1.25A 4.6m Lead
WMS8200S	1/2" Solenoid Valve DC S/S
WMS8302	Spare Parts: 1/2" DC Solenoid Seal Kit Suits Shr/Bsn
EMDS801-4.5	Spare Parts: EMD/ENM50/EMW 4.5m Extension Lead for AC/DC Powerpack
CNBSN-FF	Custodian: Basin Outlet - Wall Mount



Water Flow Projection

