

Detention: Recess Adaptor - 1/4 Turn Ceramic Disc

The water efficient Detention tapware series have been designed to provide a high level of security with the inclusion of vandal resistant features. The Detention range is constructed from dezincification resistant (DR) brass.

Incorporated is a smooth clean line chrome plated finish, which eliminates horizontal surfaces. The conical handle utilises a ceramic disc quarter turn valve. An anti rotation pin is incorporated to inhibit tampering.

PRODUCT CODES

DET608 Detention Recess Adaptor

DET608-15EXT Detention Recess Adaptor with 15mm Extended SBA



KEY FEATURES

- Quarter-turn ceramic disc
- Anti-ligature design
- Identification buttons available in Cold, Warm or Hot to suit application - specify when ordering
- Heavy duty dezincification resistant (DR) brass with durable chrome plating
- WaterMark: AS/NZS 3718 WMKA 1583

PRODUCT CODE

DET608



DET RECESS ADAPTOR



Due to ongoing Research and Development, specifications may change without notice.
Component specifications may change on some export models.
Refer to warranty statement for warranty details - www.enware.com.au/warranty.

TECHNICAL DATA

Finish	Chrome
Valve Type	Ceramic Disc
Maximum Working Temperature	85°C
Minimum Working Pressure	50kPa
Maximum Working Pressure	500kPa
Maximum Static Pressure	800kPa
Technical Notes	Maximum Static Pressure 800kPa
	Working Pressure Range 50-500kPa
	Maximum Working Temperature 85 °C



Detention: Recess Adaptor - 1/4 Turn Ceramic Disc

SPARE PARTS

DET382	Spare Parts: Detention: Recess Stuffing Box Assembly - 1/4 Turn Ceramic Disc
DET629	Spare Parts: Detention: Tools - Locking Screw Key Only - DET608
ENW03290	Det608 Less Sba
MIS592	Allen Key (3/32) Spouts Etc
MIS595	Spare Parts: Button Only (Cs Lab Etc)