

Detention: Conical Shower Wall Mounted Shower Rose

Enware's water efficient Detention tapware series have been designed to provide a high level of security with the inclusion of vandal resistant features.

PRODUCT CODES

DET660 Detention Conical Shower Wall Mounted Shower Rose with Female 1/2" Inlet

KEY FEATURES

- "Anti-ligature design
- "Anti-rotation pin incorporated to inhibit tampering
- "WELS: 3 Star (8 L/min) supplied standard. 4 Star (6 L/min) available on request - specify when ordering
- "High quality dezincification resistant (DR) brass construction
- "Chrome plated finish



PRODUCT CODE

DET660

DET CONICAL SHOWER ROSE 8LPM



Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models. Refer to warranty statement for warranty details - www.enware.com.au/warranty.

TECHNICAL DATA

WELS Category	Shower
Standard WELS	3Stars
Standard WELS Flow Rate	8L/min
First Additional WELS	4Stars
First Additional WELS Flow Rate	6L/min
Finish	Chrome
Maximum Water Temperature	70°C
Minimum Recommended Pressure	200kPa
Maximum Recommended Pressure	500kPa
Primary Flow Rate	8L/min
Inlet Connection	1/2" BSP Female
Technical Notes	Recommended Pressure 200 - 500 kPa
	Maximum Water Temperature 70°C
	Flow Rate 8.0 L/min (3 Star WELS) 6.0 L/min (4 Star WELS)
	Inlet Connection 1/2" BSP female

SPARE PARTS

MK040	MK040
MIS592	Allen Key (3/32) Spouts Etc

