

Green LED Safety Light - Non Hazardous

Enware's Green LED Light is a versatile general purpose, IP65 rated, IK10 weatherproof lighting unit. Linear LED light engines and efficient control gear provide class leading performance; protected by an IP65 impact resistant polycarbonate housing and prismatic diffuser delivering a uniform lit appearance. Enware Green LED Light has integral long life high temperature Ni-Cd battery for emergency backup.

KEY FEATURES

- L70 50,000hrs
- Fast fix mounting clips for rapid installation
- Uniform lit appearance, no shadowing
- 4000K colour temperature, CRI >80, IP65, IK10
- High efficiency 110 (Lm/W) linear LED light engines
- Long life NiCd integral emergency battery
- Impact and heat resistant prismatic polycarbonate diffuser secured with tamperproof stainless steel clips
- Lumen output exceeds traditional fluorescent technology with reduced energy consumption
- Surface mount rear brackets supplied
- Two 20mm cable entries, one each end, supplied with IP gland
- Features a test button for a quick confidence test of emergency battery




PRODUCT CODE

ELEDNH	Green LED Safety Light - Non Hazardous
--------	--

Green LED Safety Light - Non Hazardous

TECHNICAL DATA

Operation mode	Mains, emergency maintained
Operation voltage	240V/ 50Hz, 19W - 42W
Lamp detail	LED 18W - 40W 2100lm, 4000K HF
Rating	IP65, IK10
Certification	AS 2293:2005, AS/NZS CISPR15, AS/NZS 60598.2.1
Standard materials	Body – PC, Diffuser – PC
Weight	2.3 kg



Due to ongoing Research and Development, specifications may change without notice.
Component specifications may change on some export models.
Refer to warranty statement for warranty details - www.enware.com.au/warranty.