

Wall Mounted Sensor Tap: Hands-Free On/Off Demand Sensor - 205mm Spout

The Touch-Free Wall Mounted Sensor is a sensor operated, hands-free tap that is installed above sinks and basins. It operates by sensing a hand, placed within 5 cm of the sensor unit. It uses a beam of invisible Infrared light which, when reflected from hand back to the sensor, operates the unit.

KEY FEATURES

- To turn tap on, place hand in front of sensor for half a second
- To turn off tap, place hand in front of sensor again for half a second
- Valve stays open without the hand remaining in the sensor range
- Maximum flow time 45 seconds*, reduces waste and overflow if accidentally activated
- Equipped with automatic hygiene flush function (1-10min /24hr) - enabled on request*
- Stainless steel sensor plate
- Fixed 205mm spout with 6 Star (4.5 L/min) laminar flow concealed aerator

* Longer flow times, hygiene flush function and other program settings are available at the time of ordering. Contact Enware for more information.



PRODUCT CODE

ENM5072A-205

Wall Mounted Sensor Tap: Hands-Free On/Off Demand Sensor - 205mm Spout



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.


Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.

Wall Mounted Sensor Tap: Hands-Free On/Off Demand Sensor - 205mm Spout

TECHNICAL DATA

Standard WELS	6 Stars
Standard WELS Flow Rate	5.5L/min
Maximum Thermostatic Temperature	70°C
Minimum Recommended Pressure	100kPa
Maximum Recommended Pressure	500kPa
Inlet Connection	15mm (1/2") BSP
Flow Time	<p>Place hand in sensor range to activate.</p> <p>Place hand in sensor range again to stop.</p> <p>Maximum of 45 seconds time out per activation *.</p>
Sensor Range	20-100mm
Operating Voltage	24VDC
Maximum Current	1A
Power Consumption - Maximum Load	10W
Sensor Min / Max Ambient Temperature:	Minimum: -5 °C, Maximum: 50 °C
Sensor Protection Rating:	IP67 for the front panel and sensor lens. No IP rating behind panel.
* Timing can be adjusted by use of a remote control- this is best achieved in the Enware factory, but can be performed on site- service call is required and may incur costs. There are limits to adjustability- not all requests can be accommodated.	



OPTIONAL ACCESSORIES

EMDS801	Spare Parts: EMD Touch-Activated Control Kits - 2m Extension Lead
---------	---

Wall Mounted Sensor Tap: Hands-Free On/Off Demand Sensor - 205mm Spout

SPARE PARTS

ENMS133A	Spare Parts: On Demand Sensor and Plate Only
EMDS802	Spare Parts: EMD Touch-Activated Control Kits - Transformer Piezo 24VDC 1.25A 4.6m Lead
WMS8200S	1/2" Solenoid Valve DC S/S
WMS8302	Spare Parts: 1/2"DC Solenoid Seal Kit Suits Shr/Bsn
EMDS801-4.5	Spare Parts: EMD/ENM50/EMW 4.5m Extension Lead for AC/DC Powerpack
SPC205-SP	Cache Wall Mounted Fixed Spout for Wall Sensor - 205mm

