

Food Service Pre-Rinse Unit Wall Mounted with Concealed Mixer and Pot Filler - Compact

Designed for commercial kitchens and food preparation areas, the Enware Ultra Rinse range offers durable, hygienic pre-rinse solutions to suit a variety of plumbing layouts. This compact pre-rinse assembly is ideal for installations where space is limited, while still delivering the performance required in demanding kitchen environments.

The Ultra-Rinse trigger spray delivers faster, more efficient rinsing while using less water, helping improve productivity in busy kitchens. Heavy-duty construction, chrome-plated finishes, and vandal-resistant fittings provide long-lasting performance and easy cleaning. Its compact design makes installation simple in both new and existing kitchens.

A full range of replacement parts, including hoses, trigger sprays, spindles, and handles, helps minimise downtime and keep kitchen operations running efficiently.

KEY FEATURES

- Compact design ideal for space-constrained commercial kitchens and food preparation areas.
- Exposed, wall-mounted dual mixer with colour-coded hot and cold taps, delivering hot, cold, or tempered water.
- Ultra-Rinse spray gun delivers faster, more efficient rinsing for improved productivity in busy commercial kitchens.
- Dual check valves for backflow protection.
- Spring-return hose system retracts neatly when not in use.
- Includes pot filler installed.
- Heavy-duty, serviceable quarter-turn jumper valve spindles.
- Lead-free brass body with durable chrome-plated finish.
- Modular design for flexible configuration and customisation.
- Note 1: Taps should be turned off after use, particularly overnight, to prevent over-pressurisation of downstream fittings, connections, and hoses.
- Note 2: Extended depth spindles are no longer available. Consider using exposed mixer sets (FWS031/FWS131).



PRODUCT CODE

FWS121W

Food Service Pre-Rinse Unit Wall Mounted with Concealed Mixer and Pot Filler - Compact



Food Service Pre-Rinse Unit Wall Mounted with Concealed Mixer and Pot Filler - Compact



TECHNICAL DATA

WELS Category	Tapware
Standard WELS	6 Stars
Standard WELS Flow Rate	4L/min
Finish	Chrome
Valve Type	1/4 Turn Jumper Valve
Maximum Working Temperature	70°C
Minimum Recommended Pressure	100kPa
Maximum Recommended Pressure	500kPa
Maximum Static Pressure	800kPa
Pot Filler Flow Rate	5L/min
Trigger Spray Flow Rate	4L/min
Material	Brass, Stainless Steel

Technical Notes

Ensure spring return and hose movement is not impeded by surrounding equipment, benches and shelving.


Applying excessive pulling force may damage the hose assembly



OPTIONAL ACCESSORIES

FS729SS-KIT	FS729SS-KIT- Soft Spray conversion kit for FS729 trigger spray
-------------	--

Wall-Depth Adjustment



Food Service Pre-Rinse Unit Wall Mounted with Concealed Mixer and Pot Filler - Compact

SPARE PARTS

FS070	Adjustable Wall Bracket - Standard
FS077NS	Service Kit Suits FS729
FS181	Spout Swivel Outlet Aerated - 230mm - 105mm Height
FS721S	Stuffing Box Assembly for FS721/ FS729
FS790	Trigger Spray Handle & Screw Replacement Part
SP192	Wall Mounted - Spout Base - Classic Outlet Range
SP301	Aerator M22 x 1 Female 8 Lpm - No.1 Standard
FS140	Food Service Hose 15mm Black 650mm
FS142	Food Service Hose Kit 650mm with Hose, Spring, Spring Retainer & Hook
FS729	Food Service Pre-Rinse Ultra Rinse Trigger Spray
FS795	Spray Nozzle and Guard for Ultra Rinse Trigger Spray
FS734	Washer Service Kit - O-Rings, Grub Screws, Aerator Suits FHS/FWS
FS063	Pot Filler Adaptor - Excluding Spout
FSJ308RTC	Food Service Lever Handle 80mm Recess Adaptor - Jumper Valve 1/4 Turn Rising SBA LTC with Colour Indicators
FSJ308RTC	Food Service Lever Handle 80mm Recess Adaptor - Jumper Valve 1/4 Turn Rising SBA LTC with Colour Indicators
JHS382LTC	Lever Action - Rising Spindle Recess Stuffing Box Assembly - 1/4 Turn Jumper Valve - LTC
JHS382RTC	Lever Action - Rising Spindle Recess Stuffing Box Assembly - 1/4 Turn Jumper Valve - RTC
FS072	Trigger Spray Hook
FS020	Wall Mounted Riser Base
FSJ378-80	Food Service - Lever Handle Only 80mm for Jumper Valve with Colour Indicators
FS066	Spring Retainer Extension M15 Female
WLJS398	Wellbeing Leva Colour Indicator Kit JV

Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.