

Delabie Knee Operated Straight Time-Flow Valve

Enware-Delabie Knee operated tapware providing hygienic hands free activation with automatic shut off.

KEY FEATURES

- Knee-operated time flow basin valve
- 15 seconds* flow time
- Provides hygienic, hands-free activation of tapware
- Reinforced control lever
- Chrome-plated solid brass body
- Solid brass wall plate with reinforced fixing via 4 stainless steel screws
- Cold or mixed water supply

* Flow times are indicative only and may vary depending on water supply pressure and flow conditions



PRODUCT CODE

TFC735

Delabie Knee Operated Straight Time-Flow Valve



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.

TECHNICAL DATA

Recommended Pressure	250kPa – 300kPa
Working Pressure Range	100kPa – 500kPa
Maximum Recommended Temperature	45°C
Maximum Working Temperature	70°C
Flow Time	15 seconds *Flow times are indicative only and may vary depending on water supply pressure and flow conditions
Flow Rate	Pre-Set 3lpm at 300kpa Adjustable 1.4lpm-6lpm
Inlet Connection	1/2" BSP (15mm) MI
Outlet Connection	1/2" BSP (15mm) MI
Valve Type	Time Flow
Finish	Chrome

