

# Wellbeing Leva 150mm Forward Bowl Hob Mounted Sink Set - Standard Sink Spout

The Wellbeing Leva range combines outstanding quality with functional, beautiful design. Ideal for Hospital and Aged Care applications, providing the benefits of easier reach, control, and enhanced hygiene with fewer gaps that can trap dirt and bacteria. The 150mm lever allows hands-free elbow operation suitable for clinical handwash and scrub sink environments where hygiene is critical.

## KEY FEATURES

- Quarter-turn, contra-rotating 150mm lever handles
- Ceramic Disc
- Swivel spout (SPC010)
- WELS 5 Star (5 L/min) laminar flow aerator
- Ergonomic sleek design 150mm lever handle ensures ease of use either by wrist or elbow
- Clear identification on all lever handles with blue, yellow or red coloured indicator collars
- Laminar flow aerator reducing the risk of airborne bacteria
- Lead Free Brass
- Robust construction for superior performance
- Designed and Engineered in Australia



## PRODUCT CODE

WLC150SINK

Wellbeing Leva 150mm Forward Bowl Hob  
Mounted Sink Set - Standard Sink Spout



Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - [www.enware.com.au/warranty](http://www.enware.com.au/warranty).

## TECHNICAL DATA

|  |                       |
|--|-----------------------|
| Inlet Connection                         | 1/2" BSP (15mm)       |
| Recommended Pressure                     | 50kPa – 500kPa        |
| Maximum Static Pressure                  | 800kPa                |
| Maximum Recommended Temperature          | 70°C                  |
| Maximum Ceramic Disc Working Temperature | 85°C                  |
| Flow Rate                                | 5 L/min               |
| Valve Type                               | 1/4 Turn Ceramic Disc |
| Finish                                   | Chrome                |

